

Datasheet P326

Battery powered manual plastic strapping tool

Battery powered plastic strapping tools



Characteristics

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	10.0 – 16.0 mm / 3/8 – 5/8"
	thicknesses	0.40 – 1.05 mm / .016 – .041"
Weight incl. battery:		3.95 kg / 8.7 lbs
Tool sizes with battery:		L350 x W122 x H130 mm / 13.8" x 4.8" x 5.1"
Average seal strength:		up to 75% (dependent on strap quality)
Type of seal:		Friction weld sealing
Strap tension:		400 – 2400 N / 90 – 540 lbs (adjustable)
Tensioning speed:		85 – 190 mm/s / 3.3 – 7.5 inch/s
Power supply:	Battery	18VDC / 3.0 Ah Li-Ion
Suspension bracket (optional)		

Advantages

- Complies with the European Safety Regulations EN 415-8
- New reinforced 18V motor
- Li-Ion battery technology
- Very high capacity of up to 600 strap cycles per battery load (dependent on strap quality and dimension)
- Battery protection
- Simple one-handed operation
- Very high tension force with adjustable tension speed
- Tension force and sealing time adjustable

Datasheet P326

Battery powered manual plastic strapping tool

Chart of types model P326

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2201	P326/10/0.4-0.64	10.0	3/8"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2202	P326/10/0.65-1.05	10.0	3/8"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2211	P326/11.1/0.4-0.64	11.1	7/16"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2212	P326/11.1/0.65-1.05	11.1	7/16"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2221	P326/12/0.4-0.64	12		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2222	P326/12/0.65-1.05	12		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2223	P326/12.7/0.4-0.64	12.7	1/2"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2224	P326/12.7/0.65-1.05	12.7	1/2"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2231	P326/13/0.4-0.64	13		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2232	P326/13/0.65-1.05	13		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2251	P326/15/0.4-0.64	15		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2252	P326/15/0.65-1.05	15		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2253	P326/15.5/0.4-0.64	15.5		0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2254	P326/15.5/0.65-1.05	15.5		0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5
43.2261	P326/16/0.4-0.64	16	5/8"	0.40-0.64	.016-.025	2400	540	85-190	3.3-7.5
43.2262	P326/16/0.65-1.05	16	5/8"	0.65-1.05	.026-.041	2400	540	85-190	3.3-7.5

Battery chargers for model P326

Item No.	Model	Charging type	Tension	Countries
N5.4443	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, (BRN), (BRU), (CY), (EAK), (EAT), (GB), (IRL), (M), (MAL), (OM), (SGP), (Y), (Z), (ZA), (ZW)
N5.4447	Battery standard charger	Li-Ion	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4445	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	AUS, NZ

(..) = Adapter required

Battery for model P326

Item No.	Model	Tension	Power
N5.4330	Accu Li-Ion	18VDC	3.0 Ah

Accessories

P32.0112	Standard suspension bracket
P32.0137	Suspension bracket for alternating positions